

ProCash 2000xe

Monofunction cash dispenser
for lobby installations



Compact design
and minimum
footprint

Bundle output of
up to 60 notes

Optimized cash
management

Designed for use
by people with
disabilities

Different
installation
versions

Comprehensive
security
solutions

Open hardware
and software
architectures"

Project-specific
solutions



Technical Data

ProCash 2000xe

Monofunction cash dispenser

The ProCash 2000xe is a compelling solution as it comes with a small footprint and delivers maximum availability.

The integrated stepper motor enables cassettes to be emptied down to the very last note.

The wide range of installation options – combined with prefabricated frames – makes it possible to install this system even in locations where space is limited.

DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- 15" TFT LCD
- Sunlight TFT LCD
- Privacy display filter

KEYBOARD

- Encrypting PIN pad (EPP V5) with 4 function keys
- PIN shield (VISA-compliant)

CARD HANDLING

- Dip hybrid card reader
- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Preparatory kit for CIM 06
- Various card retract compartments

CASH DISPENSING

- Up to 5 cassettes (sealable)
- Max. filling height per cassette: 310 mm
- Note reject/bundle retract, storage in separate compartments
- Cassettes with lock
- Cassettes with filling level recognition
- Cassette presetting

SECURITY

- Intruder alarm
- Cash slot camera
- Portrait camera
- Uninterruptible power supply
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

SAFES

- UL 291 Level 1
- CEN III / VdS / CNPP
- CEN IV
- CEN L

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)

BARCODE READER

- Able to read and process various barcode formats

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

POWER SUPPLY

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

TEMPERATURE RANGE

- + 5° C to + 40° C

RELATIVE HUMIDITY

- 5 % to 85 %

INSTALLATION

- Frontload
- Rearload
- Indoors

APPROVALS

