

**WINCOR
NIXDORF**

ProCash 2054xe

Monofunction cash dispenser
for outdoor and lobby installations



Compatible
with competitor
systems

Bundle output
up to 60 notes

Optimized cash
management

Designed for use
by people with
disabilities

15" LCD screen

Comprehensive
security
solutions

Open hardware
and software
architectures

Project-specific
solutions



Technical Data

ProCash 2054xe

Monofunction cash dispenser

The ProCash 2054xe is, like the ProCash 2050xe, an automated teller machine that has been designed for installation outdoors and in lobbies.

The focus here is not only on ergonomic layout of the individual controls but also on installation compatibility with systems from competitors.

DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- 15" TFT LCD
- Sunlight TFT LCD
- Privacy display filter

KEYBOARD

- Encrypting PIN pad (EPP V5 PCI) or alpha kombi (compact) with EPP V5 PCI
- PIN shield (VISA-compliant)

CARD HANDLING

- Dip hybrid card reader
- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Preparatory kit for CIM 06
- Various card retract compartments

CASH DISPENSING

- Up to 4 cassettes (sealable)
- Max. filling height per cassette: 310 mm
- Note reject/bundle retract, storage in separate compartments
- Cassettes with lock
- Cassettes with filling level recognition
- Cassette presetting

SECURITY

- Intruder alarm
- Cash slot camera
- Portrait camera
- Uninterruptible power supply
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

SAFES

- UL 291 Level 1
- CEN III / VdS / CNPP
- CEN IV
- CEN L

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)

BARCODE READER

- Able to read and process various barcode formats

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

POWER SUPPLY

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

TEMPERATURE RANGE

- + 5°C to + 40°C
- Customer panel vicinity - 40°C to + 50°C (with heating)

RELATIVE HUMIDITY

- 5 % to 85 %

INSTALLATION

- Rearload
- Outdoors and in lobbies

APPROVALS

