

WINCOR
NIXDORF

ProCash 2100xe

Multifunction ATM
for lobby installations



Coin deposits
in sidecar

Bundle output
up to 60 notes

Optimized cash
management


Designed for use
by people with
disabilities

Intelligent
cash and check
deposits

Comprehensive
security
solutions

Open hardware
and software
architectures

Project-specific
solutions



Technical Data

ProCash 2100xe

DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- 15" TFT LCD
- Sunlight TFT LCD
- Privacy display filter

KEYBOARD

- Encrypting PIN pad (EPP V5 PCI) or alpha kombi or multi keyboard
- PIN shield (VISA-compliant)
- Alphanumeric/EPP kombi keyboard

CARD HANDLING

- Dip hybrid card reader
- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Preparatory kit for CIM 06/MM
- Various card retract compartments

CASH DISPENSING

- Up to 4 cassettes (sealable)
- Max. filling height per cassette: 310 mm
- Cassettes with lock
- Cassettes with filling level recognition
- Cassette presetting

SECURITY

- Intruder alarm
- Cash slot camera
- Portrait camera
- Uninterruptible power supply
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

SAFES

- UL 291 Level 1
- CEN III / VdS / CNPP
- CEN IV
- CEN L

PRINTERS

- Receipt and journal printer (dot matrix or thermal)
- Statement/information printer (dot matrix or thermal)

PASSBOOK PROCESSING

- Passbooks with a horizontal fold
- ZeKoSa reading unit, page-turning function and last line recognition
- Optional retract and/or deposit compartment for passbooks and loose sheets

COIN PROCESSING

- 6 or 8 coin hoppers

BARCODE READER

- Able to read and process various barcode formats

CASH DEPOSITS

ENVELOPE DEPOSITS

- Integrated envelope dispensing
- Transaction data printed in one line
- Capacity: Up to 200 or 300 envelopes depending on the deposit compartment, optional security compartment

CASH/CHECK DEPOSIT MODULE

Banknote processing

- Input of bundles of up to 50 notes (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm or 385 mm
- Cassettes with lock
- Separate compartment for counterfeits
- Separate compartment for retracts
- Banknote validation in compliance with ECB article 6
- Metal detection

Check processing

- Input of bundles of up to 50 checks (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm or 385 mm
- Cassettes with lock
- Scanner module for single or bundled checks
 - MICR (E13B or CMC7)
 - OCR image processing

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

POWER SUPPLY

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

TEMPERATURE RANGE

- + 5°C to + 40°C

RELATIVE HUMIDITY

- 5 % to 85 %

INSTALLATION

- Frontload
- Rearload
- Indoors

APPROVALS

