

ProCash 2350xe

Multifunction ATM

Freestanding island drive-up system



Extremely robust
system design

Bundle output
up to 60 notes

Optimized cash
management

Designed for use
by people with
disabilities

Intelligent
cash and check
deposits

Comprehensive
security
solutions

Open hardware
and software
architectures

Project-specific
solutions



ProCash 2350xe

Multifunction ATM

The ProCash 2350xe island drive-up system guarantees around-the-clock service under difficult conditions, too.

A sunlight display, resistant materials and a variety of security options meet the increased demands placed on an automated teller machine that is completely free-standing.

This island drive-up system also supports automated deposits of bundles of banknotes and checks.

Technical Data

DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" sunlight TFT LCD
- Privacy display filter

KEYBOARD

- Encrypting PIN pad (EPP V5 PCI)
- PIN shield (VISA-compliant)

CARD HANDLING

- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Various card retract compartments

CASH DISPENSING

- Up to 4 cassettes (sealable)
- Max. filling height per cassette: 310 mm
- Note reject/bundle retract, storage in separate compartments
- Cassettes with lock
- Cassettes with filling level recognition
- Cassette presetting

SECURITY

- Intruder alarm
- Portrait camera
- Uninterruptible power supply
- Tamperproof card slot

- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

SAFES

- UL 291 Level 1

PRINTERS

- Receipt and journal printer
- Statement/information printer (Dot matrix or thermal technology both)

ENVELOPE DEPOSITS

- Integrated envelope dispensing
- Transaction data printed in one line
- Capacity: Up to 200 or 300 envelopes depending on the deposit compartment, optional security compartment

CASH/CHECK DEPOSIT MODULE

Banknote processing

- Input of bundles of up to 50 notes (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Separate compartment for counterfeits
- Separate compartment for retracts
- Banknote validation in compliance with ECB article 6
- Metal detection

Check deposits

- Input of bundles of up to 50 checks (unsorted)
- Up to 2 cassettes (sealable)

- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Scanner module for single or bundled checks
 - MICR (E13B or CMC7)
 - OCR image processing

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

POWER SUPPLY

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

TEMPERATURE RANGE

- + 5°C to + 40°C
- - 40°C to + 50°C (with climate control unit)

RELATIVE HUMIDITY

- 5 % to 85 %

INSTALLATION

- Frontload
- Outdoors

APPROVALS

