WINCOR NIXDORF

ProCash 3100xe

Multifunction cash recycling system for lobby installations





WINCOR NIXDORF

Technical Data

ProCash 3100xe

DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- 15" TFT LCD
- Privacy display filter

KEYBOARD

- Numeric PIN pad with 4 function keys
- Encrypting PIN pad (EPP V5) with 4 function keys
- PIN shield (VISA-compliant)
- Alphanumeric/EPP combi keyboard

CARD HANDLING

- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Preparatory kit for CIM 06 or MM
- Various card retract compartments

SECURITY

- Intruder alarm
- Portrait camera
- Cash slot camera
- Uninterruptible power supply

- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

SAFES

- UL 291 Level 1
- CEN L
- CEN III / VdS / CNPP
- CEN IV

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)

COIN PROCESSING (SIDECAR)

- Coin dispensing
 - 8 coin hoppers
- Coin deposits

BARCODE READER

Able to read and process various barcode formats

BANKNOTE PROCESSING

- Modes
- Cash dispensing
- Cash deposits
- Cash deposits/dispensing
- Cash recycling

- Input of bundles of up to 400 notes (unsorted)
- Output of bundles of up to 99 notes
- Up to 7 cassettes (sealable)
- Up to 5 drum modules for recycling.
- Max. filling height per cassette: 310 mm
- Cassettes with lock
- Cassette presetting
- Separate compartment for counterfeits
- Separate compartment for retracts
- Banknote validation in compliance with FCB article 6
- Metal detection in the input tray

ENVELOPE DEPOSITS

- Integrated envelope dispensing
- Transaction data printed in one line
- Capacity: Up to 200 envelopes, depending on filling

CHECK PROCESSING:

- Input of bundles of up to 50 checks (unsorted)
- Deposit box
- Scanner module for single or bundled checks
- MICR (E13B or CMC7)
- OCR image processing

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

Windows XP

POWER SUPPLY

110 – 120 V~/220 – 240 V~, 50 – 60 Hz

ENVIRONMENTAL CONDITIONS

TEMPERATURE RANGE

 $= +5^{\circ}C$ to $+40^{\circ}C$

RELATIVE HUMIDITY

5 % to 85 %

INSTALLATION

- Frontload
- Rearload
- Indoors

APPROVALS



Wincor Nixdorf International GmbH • Banking Division

Order No. R10306-J-Z744-2-7600

Heinz-Nixdorf-Ring 1 • D-33106 Paderborn • Germany Phone: +49 (0) 52 51 / 6 93-33 01 Info.Banking@wincor-nixdorf.com www.wincor-nixdorf.com

ProCash® is a registered trademark of Wincor Nixdorf International GmbH

© Wincor Nixdorf International GmbH