

**WINCOR**  
**NIXDORF**

# ProCash 3000

Monofunctional deposit system  
for lobby installations



Bulk deposits of  
up to 50 notes

Optimized cash  
management

Minimum  
footprint

Designed for use  
by people with  
disabilities

Intelligent  
cash and check  
deposits

Comprehensive  
security  
solutions

Open hardware  
and software  
architectures

Project-specific  
solutions



## Technical Data

## ProCash 3000

### DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- 15" TFT LCD
- Sunlight TFT LCD
- Privacy display filter

### KEYBOARD

- Numeric PIN pad with 4 function keys
- Encrypting PIN pad (EPP V5) with 4 function keys
- PIN shield (VISA-compliant)

### CARD HANDLING

- Dip hybrid card reader
- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Various card retract compartments

### SECURITY

- Intruder alarm
- Portrait camera
- Uninterruptible power supply
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader

### SAFES

- UL 291 Level 1
- CEN III / VdS / CNPP
- CEN IV

### PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)

### BARCODE READER

- Able to read and process various barcode formats

### BANKNOTE PROCESSING

- Mode
  - Cash deposits
- Input of bundles of up to 50 notes (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Separate compartment for counterfeits
- Separate compartment for retracts
- Banknote validation in compliance with ECB article 6
- Metal detection

### CHECK PROCESSING

- Input of bundles of up to 50 checks (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Scanner module for single or bundled checks
  - MICR (E13B or CMC7)
  - OCR image processing

### MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

### AUDIO

- Loudspeakers
- Headset jack

### OPERATING SYSTEM

- Windows XP

### POWER SUPPLY

110 – 120 V~/220 – 240 V~, 50 – 60 Hz

### ENVIRONMENTAL CONDITIONS

#### TEMPERATURE RANGE

- +5°C to +40°C

#### RELATIVE HUMIDITY

- 5% to 85%

### INSTALLATION

- Frontload
- Rearload
- Indoors

### APPROVALS

