

ProCash 5100

Automated teller safe
Undercounter model

Compact
design

Bundle output of
up to 60 notes

Optimized cash
management

Cash trans-
actions by several
tellers



CMD-V4
dispensing
technology

Comprehensive
security
solutions

Open hardware
and software
architectures

Project-specific
solutions



Technical Data

ProCash 5100

Automated teller safe

The ProCash 5100 is an undercounter model for installation directly at the teller's workplace or near the counter. The ProCash 5100 supports open-plan customer zones in the front office and rounds off an institution's consulting services by dispensing cash.

Cash transactions are clearly associated with the appropriate teller by lighted arrows and a numeric display near the output slot.

Electronic locks secure the optional deposit box and the safe with a dual code (according to UVV) and with time delay.

CASSETTE-BASED DISPENSING SYSTEM

- Up to 6 cash-out cassettes

OUTPUT UNIT

- Cash-out cassettes: stacking height of 310 mm
- Reject cassette: stacking height of 170 mm
- Optional security lock for cassettes

BANKNOTE PROCESSING

- Dispensing of bundles of up to 60 notes
- Dispensing rate of up to 8 notes per second
- Use of the same or different notes

SAFES

- UL291 Business Hours
- UL 291 Level 1
- CEN III

DEPOSIT UNIT

- Two manual deposit cassettes each with a stacking height of 375 mm (optional)
- Two keylocks or one electronic lock

SOFTWARE REQUIREMENTS

- MS/DOS and CSC S/OS
- Emulations
 - AK03/04
 - BBA 9927
 - BM 4733i
 - De La Rue TCDs
 - De La Rue CashMaster
 - NCR
 - Diebold
- J/BOS FO 1.3 (J/XFS)
- Windows NT 4.0/XP/2000

ATS APPLICATIONS

- FO/ATS 2.0 and above
- ProCash/FOnet 2.0 and above
- ProAKT 2.0 and above

ELECTRONIC PLATFORM

- Standard PC

VOLTAGE

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

POWER INPUT

- 350 W

TEMPERATURE RANGE

- +15° C to +35° C

RELATIVE HUMIDITY

- 10 % to 75 %

INSTALLATION

- Frontload

APPROVALS

