

ProCash 6100xe

Automated Teller Safe

Under-counter model

Under-counter
model with closed
cash cycle

Bundle deposit/
output of up
to 200 banknotes

Optimized cash
management

Comprehensive
security
solutions



Small
footprint

Fitness sorting
of banknotes

Open hardware
and software
architectures

Project-specific
solutions



Technical Data

ProCash 6100xe

Automated Teller Safe

The ProCash 6100xe is a cash recycling automated teller safe designed for "seated teller" installations. Its compact dimensions and small service area provides maximum flexibility in open branch designs.

With up to eight recycling drums the ProCash 6100xe provides high cash capacity and maximum cash management flexibility.

The ProCash 6100xe meets all current criteria for currency recognition, fitness sorting and traceability.

DRUM STORAGE SYSTEM

- 6 or 8 drum modules

OUTPUT UNIT

- Output at the center (front)

BANKNOTE PROCESSING

- Operating mode
 - Cash Recycling
- Bundle input up to 200 Banknotes (unsorted)
- Bundle output up to 200 Banknotes
- Up to 8 drum modules
 - 8x up to 500 banknotes
- Authentication
 - Visible
 - Infrared
 - Ultraviolet
 - Magnetic
- Detection systems (compliant with ECB article 6 / Framework)
 - Fitness sorting
 - Advanced banknote classification with traceability

SECURITY

- Intruder alarm system
- Robbery alarm system

SAFES

- UL291 Level 1
- CEN I
- CEN / VdS III

DEPOSIT UNIT

- Two manual drop deposits (optional)

DATA COMMUNICATION INTERFACES

- 2 serial RS-232 C interfaces
- USB
- LAN/Ethernet

SOFTWARE REQUIREMENTS

- J/BOS FO 1.3 (J/XFS)
- Windows NT 4.0/XP/2000

ATS APPLICATIONS

- FO/ATS 2.0 and above
- ProCash/FOnet 2.0 and above
- ProAKT 3.1.1.70 and above

VOLTAGE

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

POWER INPUT

- 240 W

TEMPERATURE RANGE

- +15°C to +35°C

RELATIVE HUMIDITY

- 10% to 75%

INSTALLATION

- Frontload
- Indoor

APPROVALS

