

ProPrint 1000

Monofunction customer information
and statement printer

Monofunctional

Small footprint

Short transaction
times

Ergonomic design



6 x 40 character
display

Thermal or dot
matrix printer

Open hardware
and software
architectures

Project-specific
solutions



Technical Data

ProPrint 1000

Monofunction customer
information and
statement printer

DISPLAY

- 6 x 40 character display

KEYBOARD

- Stainless-steel keyboards:
 - EPP
 - PIN pad
 - Alpha keyboard + trackball
 - Combo keyboard (alpha keyboard + EPP)
 - Multi keyboard (alpha keyboard + trackball + EPP)
- PIN shield (ZKA-/VISA-compliant)

CARD HANDLING

- Motorized hybrid card reader
- DIP hybrid card reader
- Card return after power failure
- Contactless reading method

PRINTER

- Thermal or dot matrix technology
- One or two paper trays
- Paper cutter
- Document output: bundle (max. 10 documents) with retract function

USER GUIDANCE

- Optical indicators at all input/output modules

OPTIONS

- Customizable color scheme
 - Single color
 - Multiple colors
 - RAL colors
 - Special colors
- Pull-out paper trays
- Other options on request

OPERATING SYSTEM

- Windows XP

SYSTEM CONTROL

- Standard PC (Celeron or Pentium)

CONNECTION OPTIONS

- Ethernet LAN onboard
- Ethernet LAN card
- Token Ring LAN card
- X.25 WAN card
- ISDN card

POWER SUPPLY

- 110 – 120 V~ / 220 – 240 V~
- 50 Hz – 60 Hz

ENVIRONMENTAL CONDITIONS

Temperature range:
+5° C to +35° C
Relative humidity:
5% to 85%

INSTALLATION

- Indoors
- Frontload
- Free-standing
- Niche installation

APPROVALS

