

ProPrint 2000

Multifunction customer information
and statement printer



Monofunctional
or multifunctional >

Small footprint >

Upgradable with
scanner sidecar >

Ergonomic design >

< Various display
sizes

< Thermal or dot
matrix printer

< Open hardware
and software
architectures

< Project-specific
solutions



Technical Data

ProPrint 2000

Multifunction customer
information and
statement printer

DISPLAY

- 12.1"
- 15"
- 17"
- Touchscreen or softkeys (stainless steel, Braille)
- Autoscaling
- Sunlight

KEYBOARD

- Stainless-steel keyboards:
 - EPP
 - PIN pad
 - Alpha keyboard + trackball
 - Combo keyboard (alpha keyboard + EPP)
 - Multi keyboard (alpha keyboard + trackball + EPP)
- PIN shield (ZKA-/VISA-compliant)

CARD HANDLING

- Motorized hybrid card reader
- DIP hybrid card reader
- Card return after power failure
- Contactless reading method

PRINTER

- Thermal or dot matrix technology
- One or two paper trays
- Paper cutter

- Document output: bundle (max. 10 documents) with retract function
- Ticket printer

USER GUIDANCE

- Optical indicators at all input/output modules

OPTIONS

- Camera
- Telephone handset
- Barcode scanner
- Customizable color scheme
 - Single color
 - Multiple colors
 - RAL colors
 - Special colors
- Pull-out paper compartments
- Other options on request

DOCUMENT SCANNER (AS UPGRADE IN SIDECAR)

- Money transfer form scanner
 - Recognition software for typescript and handwritten block capitals
- Check scanner
 - MICR reading
 - Front and back scanning
- Printing function (endorsement)

AUDIO

- Stereo loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

SYSTEM CONTROL

- Standard PC (Celeron or Pentium)

CONNECTION OPTIONS

- Ethernet LAN onboard
- Ethernet LAN card
- Token Ring LAN card
- X.25 WAN card
- ISDN card

POWER SUPPLY

- 110 – 120 V~ / 220 – 240 V~
- 50 Hz – 60 Hz

ENVIRONMENTAL CONDITIONS

Temperature range:
+5° C to +35° C
Relative humidity:
5% to 85%

INSTALLATION

- Indoors
- Frontload
- Free-standing
- Niche installation

APPROVALS

