CINEO C2590 Island Drive-up



Multifunctional automated teller machine for outdoor, freestanding installations

Cash Cycle Management™ Solutions – Setting new standards

The CINEO C2590 is part of the unique technology concept and a component of Wincor Nixdorf's revolutionary Cash Cycle Management™ Solutions portfolio. The cash dispenser is based on a completely new technology approach, with an innovative banknote storage concept as its core element. This makes it possible for banks and retailers to interchange one and the same cassette between all systems in the CINEO cash series.

Clear value proposition

The groundbreaking technology platform optimizes cash replenishment and pick-up processes. The new cash media dispenser enables operators to realize closed cash cycles throughout a bank branch or retail store as well as between branches/stores in one organization. And for the very first time, cash cycles can be networked across industries and integrated in cash center processes. As a result of optimized cash handling, the CINEO C2590 enables operators to cut their costs and improve on security. Combined with innovative software and end-to-end cash management services, the system guarantees audit compliance and maximum transparency of all cash inventories at all times.

The island for extremes

With its new CINEO C2590 system, Wincor Nixdorf offers yet another best-in-class cash dispenser which is designed for drive-up business. It offers outstanding performance thanks to two multifunctional areas with numerous options such as innovative print, bulk check processing as well as cash and envelope deposits. 15" monitors, which swivel to the perfect viewing angle, softkey and touch operation, an illuminated card slot, attractive design and customer guidance guarantee maximum satisfaction. It enables bank customers to handle their banking business speedily from the comfort of their cars. The system is suitable for installation in extreme climates. Optimal component accessibility and a graphical user interface make CINEO C2590 one of the world's most userfriendly cash dispensing systems. The same applies to serviceability: A broad range of operating information is delivered automatically,

enabling proactive and efficient system management. Dispenser technology that has proven its worth across the globe, coupled with the cutting-edge cassette technology, conspire to create a unique, flexible system that can be tailored to customers' specific needs.

Security across the board

CINEO C2590 offers impressive new security features: A tamper-proof card slot, the Anti-Skimming II Module, high-resolution cameras, Optical Security Guard, Anti-Cash-Trapping sensors, CrypTA Stick and EPP V6 with privacy shield, are all features that close potential security gaps, improve system availability and win customer confidence.





Services

Wincor Nixdorf's fast, professional manufacturer service is available as an option for the CINEO C2590 as part of the complete solution offer. Tailored services enable the highest possible system availability and security worldwide due to standardized service processes and efficient remote management based on the Wincor Nixdorf eServices Platform®. By request banks can hand over their complete IT operations and the control of their cash processes to Wincor Nixdorf's service organization.

Consulting and integration

Wincor Nixdorf offers a fast and optimal business implementation – from analysis and concept design through to optimal deployment and integration in individual customer scenarios. In Professional Services from Wincor Nixdorf you find an ideal partner for implementing your retail banking process and IT strategy.

Published by

Wincor Nixdorf International GmbH

Heinz-Nixdorf-Ring 1 33106 Paderborn Germany

Phone: +49 (0) 52 51 / 6 93-30 Fax: +49 (0) 52 51 / 6 93-77 30 info.banking@wincor-nixdorf.com

www.wincor-nixdorf.com

© Wincor Nixdorf International GmbH

Order No. R10616-J-Z744-1-7600 Printed in Germany, April 2013

TECHNICAL DATA

General

Installation types

- Outdoor Island Drive-up frontload
- Freestanding

Chassis

- Multicolor options
- Illuminated advertising area
- Customers guided by optical indicators at all input and output modules

Banknote processing

Cash out module

- Withdrawals of up to 60 notes in a bundle
- Banknote reject/bundle retract

Banknote storage

- 2 4 cassettes
- Maximum fill level 300 mm
- Fill level indicator
- Scalable cassette concept:
 Lock, lead seal, tamper indicator,
 shutter and cover monitoring, cash
 management memory
- Retract/reject cassette with 2 compartments

Customer interaction

Display

- 15" TFT LCD display as standard, high bright
- Swivel LCD display (manual or automatic via face recognition)
- Autoscaling function for automatic VGA, SVGA, XGA adjustment
- 8 softkeys and/or touch display Keyboard

EPP V6 (ZKA & PCI 1.x/2.x certified)

Card processing

- Hybrid motorized EMV 4.x Level 1
- Illuminated throat
- Card retracted if not removed
- Card returned if power fails
- HiCo-write function (opt.)
- Integrated contactless reader (opt.)
- Contactless card reader (external integration/EMV 2000 certified)

Receipt/journal printer

- Thermal printer (dual color for document printing, dual roll receipt printer)
- Dot matrix printer

Audio

 Loudspeakers, headset jack with adjustable volume

Security

Cash security

- Safe: UL 291 Level 1
- Intruder alarm system
- Anti-Cash-Trapping Sensors

Data and software security

- Secure channel
- Anti-Manipulation Card Slot
- Anti-Skimming II Module
- EPP shield (ZKA/VISA-compliant)
- Awareness mirror
- Privacy display filter for the monitor

Identity and access control

- Intelligent operator authentification via CrypTA Stick
- Mechanical and electronic locks
- Anti-Card-Trapping functionality
- Biometric options

Security monitoring

- Cash slot, portrait, ID card unit camera
- Optical Security Guard (OSG)

Multifunctionality

Cash/Check Deposit Module

- Deposit of bundles of up to 50 notes/checks
- MICR- and OCR recognition
- Metal detection
- Banknote validation in compliance with ECB Article 6
- Options: Fit/unfit test
- Cassette with lock
- Max. fill level per cassette: 215 mm
- Separate compartment for counterfeit notes
- Separate compartment for retracts

Envelope deposit

Statement/information printer

- Thermal two-color printer
- Retract function with storage compartment
- Paper type z-fold

Barcode reader

1D and 2D barcodes

Service

Operator panel

- 10,4" graphical color display
- Operator keyboard

Operator guidance

 User guidance via graphic animations and color guidance

Operation

Environmental conditions

- Fascia without heating:
 - Temperature range: +5 °C to +40 °C
- Humidity: 10 % to 85 %
- Fascia with heating:
- Temperature range: -40 °C to +50 °C
- Humidity: 5 % to 85 %

Technical details

- Supply voltage range:
 110 120 V; 220 240 V
- Mains frequency: 50/60 Hz
- Uninterruptable Power Supply